

North Myrtle Beach Quarry
 3990 Highway 9 East
 Loris, SC 29569
 843-756-3400



www.wakestonecorp.com

Contact:
 Hunter Jenkins, Sales Representative
hjenkins@wakestonecorp.com
 (cell) - 843-241-5883

Product Data Sheet

Product: Feed Grade Calcium Carbonate (14 x 120 Fine Grind)

Product Code: FGCC-1

Wake Stone Feed Grade Calcium Carbonate is mined from a marine limestone source located in Loris, South Carolina. The calcium carbonate average is 92 %, but values are subject to variations in the deposit. Feed Grade Calcium Carbonate is a product added to animal feeds and provides a great source of soluble calcium.

Typical Property Results

Mechanical Sieve Analysis	Chemical Analysis	Physical Properties																																																		
<table border="1"> <thead> <tr> <th>Square Opening</th> <th>% Passing</th> </tr> </thead> <tbody> <tr> <td>#10 (2.00mm)</td> <td>100</td> </tr> <tr> <td>#16 (1.18mm)</td> <td>88</td> </tr> <tr> <td>#20 (0.84mm)</td> <td>61</td> </tr> <tr> <td>#30 (0.06mm)</td> <td>30</td> </tr> <tr> <td>#50 (0.30mm)</td> <td>10</td> </tr> <tr> <td>#100 (0.150mm)</td> <td>6</td> </tr> <tr> <td>#200 (0.075mm)</td> <td>4</td> </tr> </tbody> </table>	Square Opening	% Passing	#10 (2.00mm)	100	#16 (1.18mm)	88	#20 (0.84mm)	61	#30 (0.06mm)	30	#50 (0.30mm)	10	#100 (0.150mm)	6	#200 (0.075mm)	4	<table border="1"> <tbody> <tr> <td>Calcium</td> <td>36.00%</td> </tr> <tr> <td>Calcium Solubility</td> <td>56.00%</td> </tr> <tr> <td>Phosphorus</td> <td>0.10%</td> </tr> <tr> <td>Sodium</td> <td>0.12%</td> </tr> <tr> <td>Magnesium</td> <td>0.48%</td> </tr> <tr> <td>Manganese</td> <td>69.0 ppm</td> </tr> <tr> <td>Iron</td> <td>2720 ppm</td> </tr> <tr> <td>Zinc</td> <td>3.1 ppm</td> </tr> <tr> <td>Copper</td> <td>16.6 ppm</td> </tr> <tr> <td>Potassium</td> <td>127 ppm</td> </tr> <tr> <td>Sulfur</td> <td>0.291%</td> </tr> <tr> <td>Aluminum</td> <td>500.00 ppm</td> </tr> </tbody> </table>	Calcium	36.00%	Calcium Solubility	56.00%	Phosphorus	0.10%	Sodium	0.12%	Magnesium	0.48%	Manganese	69.0 ppm	Iron	2720 ppm	Zinc	3.1 ppm	Copper	16.6 ppm	Potassium	127 ppm	Sulfur	0.291%	Aluminum	500.00 ppm	<table border="1"> <tbody> <tr> <td>ASTM C 29</td> <td></td> </tr> <tr> <td>Compacted (rodded) Density</td> <td>82.34 pcf</td> </tr> <tr> <td>ASTM C 29</td> <td></td> </tr> <tr> <td>Loose Density</td> <td>75.06 pcf</td> </tr> <tr> <td>Current Moisture Content</td> <td>0.65%</td> </tr> </tbody> </table>	ASTM C 29		Compacted (rodded) Density	82.34 pcf	ASTM C 29		Loose Density	75.06 pcf	Current Moisture Content	0.65%
Square Opening	% Passing																																																			
#10 (2.00mm)	100																																																			
#16 (1.18mm)	88																																																			
#20 (0.84mm)	61																																																			
#30 (0.06mm)	30																																																			
#50 (0.30mm)	10																																																			
#100 (0.150mm)	6																																																			
#200 (0.075mm)	4																																																			
Calcium	36.00%																																																			
Calcium Solubility	56.00%																																																			
Phosphorus	0.10%																																																			
Sodium	0.12%																																																			
Magnesium	0.48%																																																			
Manganese	69.0 ppm																																																			
Iron	2720 ppm																																																			
Zinc	3.1 ppm																																																			
Copper	16.6 ppm																																																			
Potassium	127 ppm																																																			
Sulfur	0.291%																																																			
Aluminum	500.00 ppm																																																			
ASTM C 29																																																				
Compacted (rodded) Density	82.34 pcf																																																			
ASTM C 29																																																				
Loose Density	75.06 pcf																																																			
Current Moisture Content	0.65%																																																			

Feed Label Information: Feed grade calcium carbonate is listed by the Association of American Feed Control Officials as feed ingredient number 57.10. The Food and Drug Administration recognizes calcium carbonate as being G.R.A.S (Generally Recognized as Safe). Calcium carbonate is also approved as meeting "organic" specifications under the National Organic Program guidelines. All Wake Stone feed grade calcium carbonate products meet these designations. Provide fresh clean water at all times

All information provided and recommendations made are intended to assist customers in determining if our product is suitable for their application. It is the customer's responsibility to inspect and test our product before use to make their own decision regarding suitability. We do not guarantee results of product for any suggested application with respect to use of any formula or material described herein.